

Ultrasonic Cleaning

Sonicpro Fact Sheet



Vortexx Parts Dryer



Vortexx TD-8000 Dryer

Tank Material: 304 Stainless Steel
Entry opening: 22"W x 17.5"H
Overall DIM: 57"L x 24"W x 68"H

Description

Double walled and insulated Stainless Steel Construction. Dual heaters provide 8000 Watts of Vortexx drying power facilitating fast production drying. Dual 9 inch fans provide even heat distribution throughout the drying chamber. Digital heat controller with safety shutoff prevents overheating. Soft entry/exit dryer panels facilitates effortless parts basket pass thru.



3000-C Chamber Dryer

Tank Material: 304 Stainless Steel
Chamber ID: 30"L x 22"W x 17"D
Unit OD: 36"L x 35.5"W x 35"H

Description

Stainless Steel insulated drying chamber
Insulated Stainless Steel lid with lift assist
HEAVY Duty Locking Casters
Stainless Steel Bottom Parts Grate
110 V Operation Amp Draw 15

The 3000-C dryer speeds up the parts cleaning process, dramatically decreasing drying times over standard air dry methods. The C-4 blower delivers pre-heated air via three strategically placed stainless steel diffuser bars. This drying chamber accommodates several small parts baskets or one large 24"L x 20"W x 16"H parts basket.